Accessories

	DK-S	DK20φ	DT	U	LY	LT	MG
PSC (AC adapter) PSC-21 (for Japan only: 100 V) PSC-22 (for the US only: 120 V) PSC-23 (for Europe and other countries : 220 to 240 V) Provided with Europlug cable	—	—	—	—	●	—	—
CE (extension cable) CE08-1(1m) CE08-3(3m) CE08-5(5m) CE08-10(10m) CE08-15(15m)	●	●	●				
(Conversion cable for counter connection) CE29 CE29-003(0.3m) CE29-01(1m) CE29-03(3m) CE29-05(5m) CE29-10(10m)	●	●	—				
Extension cable, bare leads CE22-01(1m) CE22-03(3m) CE22-05(5m) CE22-10(10m)	●	●					
LZ LZ71-B (BCD unit) LZ71-KR (relay/open collector) LZ61	—	—	—	—	● LY71 only (LZ71-B, KR)	—	— ● For MG10 (LZ61)

	DK-S	DK20φ	DT	U	LY	LT	MG
SZ (conversion cable) SZ70-1 (for LY71 and 72) SZ70-2 (for LT30)	—	—	—	—	●	●	—
MZ (link cable) MZ41-R5(0.5m) MZ41-01(1m) MZ41-02(2m) MZ41-05(5m) MZ41-10(10m)							● MG41
CK (High-flex extension cable) CK-T12(1m) CK-T13(3m) CK-T14(5m) CK-T15(10m) CK-T16(15m)	●	●	●	—	—	—	—

DZ

DZ252
DZ253A
DZ254
DZ174-010
DZ174-025
DZ174-050
DZ176
DZ521
DZ830F
DZ-161
DZ830B
DZ830BV
DZ-123
DZ-121
DZ-191
DZ-181
DZ-5100
DZ-122
DZ-100
DZ531
DZ581

Cable for DZ252 RS232C
(For LT and U Series) round 8-pin male ⇔D-sub 9-pin female

Cable for DZ253A RS-232C
(For LT and U Series) round 8-pin male ⇔D-sub 25-pin male

Cable for DZ254 RS-232C
(For LT and U Series) round 8-pin male ⇔bare wires

DZ174-010/DZ174-025/DZ174-050 (for DK10, 25, and 50)

DZ176 air lifter
(For DT512, 12)

DZ521
(Digital gauge stand)

Measuring units to be used	A	B
DK10NR5, PR5	32.5	75.5
DK10PLR5	32.5	56
DK25NR5, PR5	47.5	118
DK25NLR5, PLR5	47.5	98.5
DK50NR5/PR5	72	200

DZ830F (for DK830)

DZ-161 lift lever

DZ830BL (bellows set for DK830SLR)

DZ830BV (bellows set for DK830SVR)

Digital gauge stand DZ-531 (for DK110)
Surface plate material: gabbro
Surface plate flatness: 3μm
Surface plate size: 350(W)×350(D)mm
Maximum workpiece height: approx. 330 mm
Gauge mounting hole: φ20mm
Mass: 38kg

Measuring force balancer DZ-581 (for DK110)

Weight
No weight: 1.55±0.15N(155±15gf)
B:1.0±0.15N(100±15gf)
B+A:0.7±0.15N(70±15gf)
B+C:0.3±0.15N(30±15gf)

Feeler set DZ-5100
(Not including DK155/205)
* Four types of feelers shown above are provided as a set.

Plastic spherical feeler
Contact point: 3 mm/0.118" nylon

Carbide flat feeler

Off-center feeler
Contact point: 1 mm/0.039" steel ball

Pin feeler

Feeler DZ-123 (not including DK155/205)
Contact point: 3 mm/0.118" carbide ball tip
(Mounting screw: M2.5 0.45)

Coupling DZ-191

Feeler DZ-122 (for DK10, 25, and 50)
Contact point: 2.5 mm/0.098" carbide ball tip
(Mounting screw: M2.5 0.45)

Feeler DZ-121 (for DK100/110)
Contact point: 2.5 mm/0.098" carbide ball tip
(Mounting screw: M2.5 0.45)

Magnetic feeler DZ-181 (for DK155/205)

Roller feeler DZ-100 (not including DK155/205)